



**SHERWIN
WILLIAMS.**



108.22

ProGREEN 200™

Low VOC

INTERIOR LATEX PRIMER

B28W600

As of 09/22/08, Complies with:			
OTC	Yes	LEED® Clv2.0	Yes
SCAQMD	Yes	LEED® NCv2.2	Yes
CARB	Yes	LEED® SCv2.0	Yes
MPI Spec #	50	LEED® H	Yes
NAHB	Yes		

CHARACTERISTICS

ProGreen 200 Low Odor Interior Latex Primer is a durable, professional quality, interior vinyl acrylic primer for use on walls and ceilings of plaster, wallboard, and masonry. You can use this product, without typical odor complaints, in occupied areas because of the very low odor during application and drying.

ProGreen 200 Low Odor Interior Latex Primer meets or exceeds the criteria set forth by the U. S. Green Building Council LEED-CI, Version 2.0 and LEED-NC Version 2.2. All results have been verified by our ISO 9001 Laboratory

Color: White
Coverage: 350 - 400 sq ft/gal
 @ 4 mils wet; 1.5 mils dry
Drying Time, @ 77°F, 50% RH:
 Drying and recoat times are temperature, humidity and film thickness dependent.
 Touch: 1 hour
 Recoat: 4 hours
Flash Point: N/A
Finish: 0 - 5 units @ 85°
Vehicle Type: Vinyl Acrylic
B28W00600
VOC (EPA Method 24):
 43 g/L; 0.36 lb/gal
Volume Solids: 39 ± 2%
Water Vapor Permeance
 ASTM E96 A 3.9 perms
Weight Solids: 59 ± 2%
Weight per Gallon: 12.4 lb
Tinting - For best color development, use the recommended "P"-shade primer. If desired, up to 4 oz per gallon of Blend-A-Color Toner can be used to approximate the topcoat color. Check color before use. Addition of Blend-A-Color Toner may increase the VOC.

SPECIFICATIONS

This primer has been designed for use with the ProGreen 200 Interior Latex topcoats providing a complete low odor/low VOC system. If desired, you can topcoat with any Sherwin-Williams interior latex or oil architectural topcoat.

APPLICATION

Use at temperatures above 50°F. No reduction necessary.
Brush - Use a nylon/polyester brush.
Roller - Use a 3/8" - 3/4" nap synthetic cover.
Spray - Airless
 Pressure 2000 psi
 Tip017"-.021"

CLEANUP INFORMATION

Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. Flush spray equipment after cleaning with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer.

Drywall

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Masonry surfaces must be dry before priming. Moisture content must be 15% or lower and the pH between 5 and 9. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with PrepRite® Masonry Primer.

108.22

ProGREEN 200™

Low VOC

INTERIOR LATEX PRIMER

B28W600



**SHERWIN
WILLIAMS.**

SURFACE PREPARATION

Plaster

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

CAUTIONS

For interior use only.
Protect from freezing.
Non-photochemically reactive.

CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 09/22/2008 B28W00600 05 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.